Dept. of Development Services
Planning Services Division
2345 Providence Boulevard
Deltona, FL 32725
(386) 878-8600, Fax (386) 878-8621

PERMIT NO.: _____

ADDRESS: _____

APPLICANT NAME: _____
(Do NOT write in this box—for office use only!)

CITY OF DELTONA
APPLICATION FOR LAWN PROTECTION DEVICES

APPLICANT INFORMATION:

Applicant name: _____

Applicant address: _____

City/state/zip: _____

Site Address: _____

Parcel I.D. Number: _____

Applicant phone: _____ Email: _____

PURSUANT TO CHAPTER 556, FLORIDA STATUES, AS AMENDED, AN EXCAVATOR OF THE WORK PERFORMED UNDER THE SCOPE OF THIS APPLICATION SHALL CALL THE "SUNSHINE STATE ONE-CALL OF FLORIDA, INC." AT 1-800-432-4770, NOT LESS THAN TWO NOR MORE THAN FIVE BUSINESS DAYS BEFORE BEGINNING EXCAVATION.

Number of posts to be placed in ROW: _____

Applicant must provide a copy of their survey showing location of markers.

Applicant's Signature: _____ Date: _____

*******FOR OFFICIAL USE ONLY*******

Approved by: _____ Date: _____

Title: _____

CITY OF DELTONA
ADMINISTRATIVE POLICY/PROCEDURE

EFFECTIVE DATE	POLICY NUMBER	PAGE NUMBER	SUPERSEDES POLICY
4-16-02	CW02-01	1 of 2	Dated: N/A

Subject:

Right-of-Way Lawn Protection Devices

Approved by:

City Manager

4/16/02
Date

LAWN PROTECTION MARKERS

EXAMPLE

The City of Deltona recognizes a need amongst some residents to preserve their investment in the appearance of the Public R-O-W adjacent to their homes. Residents who wish to install standard, small red reflector markers, available at many local stores can do so without obtaining permission from the City. However, those who wish to install a different type of marker must adhere to the following provisions:

1. Residents must make application with the Department of Development Services and obtain their approval subject to criteria established by the City Engineer or his/her designee.
2. No impediments of any type or style shall be placed within 2 ft. of the edge of the pavement.
3. Devices desired for the purpose of protecting the lawn, shall be limited to standard markers and shall require a Use Permit for installation. The cost of the permitted objects in the right-of-way shall be the responsibility of the resident.
4. The type and style of the lawn protection markers shall conform to the following criteria:

    a. Height shall be no greater than 3 ft.
    b. Spacing of markers shall be no less than 10 feet on straight segments of roadway and four feet along corners and curves.
    c. Markers shall be constructed of a corrosion and mildew resistant material, possessing no sharp points or edges.
    d. Installation of the markers shall not result in an adverse impact on the functional grade-lines or stormwater diversion characteristics of swales.
    e. Markers shall not be anchored in concrete nor extend greater than 18 inches below grade.
    f. All markers shall have two strips of 2" wide reflector tape placed 3 inches apart around the top part of the marker.

Materials or structures in the right-of-way that are deemed a safety hazard and/or deemed an impediment to drainage must be removed. Determination of a hazard situation will be the responsibility of the City and includes, but is not limited to obstruction to visibility, City Land Development Code Section 96-37 (7).

Items may also be removed as needed for road of stormwater swale improvements with proper notice to the adjacent property owners. In any case regarding the removal of lawn protection markers, affected residents will be pre-notified of such action by door hanger or personal contact.

THERE IS A $15.00 APPLICATION FEE FOR THIS PERMIT

CITY RULES FOR INSTALLATION OF LAWN PROTECTION MARKERS

No impediments of any type or style shall be placed within 2 feet of the edge of the pavement.

Height shall be no greater than 3 feet.

Spacing of the markers shall be no less than 10 feet on straight segments of roadway and 4 feet along corners and curves.

Markers shall be constructed of a corrosion and mildew resistant material, possessing no sharp points or edges.

Installation of the markers shall not result in an adverse impact on the grade-lines (i.e., storm-water diversion characteristics) of swales.

Markers shall not be anchored in concrete nor extend greater than 18 inches below grade.

All markers shall have two strips of 2" wide reflector tape placed 3 inches apart around the top portion of the marker.

SUGGESTED MATERIALS AND METHOD OF CONSTRUCTION:

Measure the curve and straightaway section to determine how many markers (posts) you will need under the above guidelines.

3/4" SCHED 40 PVC (purchase in 10 ft. lengths) in sufficient quantity to cover area. Cut in 30-inch lengths to get four posts from each 10-foot section.

3/4" PVC caps to cover each post (plus a few extras).